

MAGNETIC BLOCK WITHOUT ON/OFF CONTR. TYPE BM3

REF 13.23

{ERREUR : balise [PRESTATION_CRITERE_ASOUST] inconnue}

Rugged construction / Waterproof construction / Force: : 80 N/cm² / Longer life

Grinding, EDM

- . 2 to 3 workholding faces
- . Without ON/Off mechanism
- . pole pitch: 4mm, except 13.23.4 = 1,3mm
- . Admissible wear of active face
- 14 mm: BM3-1; -2; -1S; 2S
- 6 mm: BM3-3; -4; 3S

D = quantity and dimensions of active faces

Options

On special request, delivered with reinforced magnetic system
model S: force=180N/cm² - pole pitch=4 mm

Reference	Poids en kg	A	B	C	D
13.23.1	3.2	100	100	50	1-100x100 + 2-100x50
13.23.1S	3.2	100	100	50	1-100x100 + 2-100x50
13.23.2	1.6	100	50	50	2-100x50 + 1-100x50
13.23.2S	1.6	100	50	50	2-100x50 + 1-100x50
13.23.3	0.4	100	25	25	2-100x25
13.23.3S	0.4	100	25	25	2-100x25
13.23.4	0.4	100	25	25	2-100x25

D = Nb workholding faces

